

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (Currently Amended): Piston pin bearing for pistons of an internal combustion engine, having pin bores (2) in which a piston pin is mounted, whereby the pin bores have a mantle surface (2.1) having a highly oval shape in extending over a region delimited by the pin boss equator - pin boss zenith - pin boss equator ~~region~~, and a mantle surface (2.2) having a circular-cylindrical shape ~~in~~ extending over a region delimited by the pin boss equator - pin boss nadir - pin boss equator ~~region~~, whose mantle lines (3, 4) running in the nadir and the zenith are oriented parallel to one another, wherein

the mantle line (3) of the highly oval mantle surface running in the pin boss zenith runs at an incline relative to the pin boss axis ~~(Z)~~ (X) on the piston side, from radially outside to radially inside, at an angle (b), in such a manner that the greatest ovality defined by its oval diameter occurs at the inner ends (7) of the pin bores, in each instance, and does not exceed

a predetermined value of the oval diameter.

Claim 2 (Previously Presented): Piston pin bearing according to claim 1, wherein the incline of the mantle line (3) determined by the angle (b) comprises only a partial region (2.3) of the pin bores (2).

Claim 3 (Previously Presented): Piston pin bearing according to claim 1, wherein the incline of the mantle line (3) determined by the angle (b) runs in linear manner.

Claim 4 (Previously Presented): Piston pin bearing according to claim 1, wherein the incline of the mantle line runs in polygonal manner, with a polygon angle of 2.5 angle minutes, in each instance.

Claim 5 (Currently Amended): Piston pin bearing according to claim 2, wherein the partial region (2.4) of the pin bores ~~(2.4)~~ (2) that is not configured in highly oval manner is configured as a circular cylinder.

Claim 6 (Previously Presented): Piston pin bearing according to claim 1, wherein the pin bores (2) have molded bore regions.

Claim 7 (Currently Amended): Piston pin bearing according to claim 1, wherein the mantle surface having a highly oval shape ~~runs in~~ is disposed between a region (10) that is delimited by a half-circle having a pin bore diameter (D) defined between pin boss equator - pin boss nadir - pin boss equator, and a half-circle having the diameter (D), offset in the direction of the pin boss zenith, along the piston axis (Y), by 0.03 percent to 0.5 percent of the defined pin boss diameter (D).

Claim 8 (Currently Amended): Piston pin bearing according to claim 7, wherein the offset (Y') amounts to between ~~0.03 and 0.5 percent, preferably~~ 0.1 and 0.15 percent of the pin bore diameter.

Claim 9 (Previously Presented): Piston pin bearing according to claim 1, wherein oil grooves, pockets, slots, or oil bores for feeding in lubricant oil are disposed in the pin bores (2).